



S008

Light cold protection



PERFORMANCE LEVELS

EN388 : 4232						
ABRASION	0	1	2	3	4	
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
CUT TDM TEST NEW EN388	A	B	C	D	E	F
IMPACT	X			P		

NORME EN 388

Gloves giving protection from mechanical risks

a b c d

The pictogram is accompanied by a 4-digit code, 4 or 5 being the best resistance rating.

- a Resistance to abrasion
Between 0 and 4 based on the number of cycles required to abrade through the sample glove (abrasion by sandpaper under a stipulated pressure).
- b Blade cut resistance
Between 0 and 5, based on the number of cycles required to cut through the sample at a constant speed.
- c Tear resistance
Between 0 and 4, based on the amount of force required to tear the sample.
- d Puncture resistance
Between 0 and 4, based on the amount of force required to pierce the sample with a standard sized point.

X means that this performance is not tested.



BCL GLOVE LTD
21 Parc-Industriel, Saint-Pacôme
(Quebec) Canada G0L 3X0
T 418 852-2098 F 418 852-3330
info@akka.ca www.akka.ca



BENEFITS

- Excellent abrasion resistance 4/4
- Cold resistant in mild weather
- Excellent dexterity
- Flexibility
- Very comfortable

APPLICATIONS

- Outside work in spring and autumn
- General handling

