

S02Y



General works

TECHNICAL CHARACTERISTICS

- Polyester glove
- Latex coated palm and fingers
- Seamless
- Elastic wrist

SIZES : 8. 9. 10. 11

PACKAGING : Dozen | 120 pairs/ box

BENEFITS

- Good resistance to abrasion
- Very good resistance to tear 4/4
- Excellent grip
- Durability
- Dexterity

APPLICATIONS

- Construction
- Heavy handling
- Roofing
- Landscaping

PERFORMANCE LEVELS

EN388 : 2242						
ABRASION	0	1	2	3	4	
CUT	0	1	2	3	4	5
TEAR	0	1	2	3	4	
PUNCTURE	0	1	2	3	4	
CUT TDM TEST NEW EN388	A	B	C	D	E	F
IMPACT	X			P		



NORME EN 388

Gloves giving protection from mechanical risks

a b c d

The pictogram is accompanied by a 4-digit code, 4 or 5 being the best resistance rating.

- a** Resistance to abrasion
Between 0 and 4 based on the number of cycles required to abrade through the sample glove (abrasion by sandpaper under a stipulated pressure).
- b** Blade cut resistance
Between 0 and 5, based on the number of cycles required to cut through the sample at a constant speed.
- c** Tear resistance
Between 0 and 4, based on the amount of force required to tear the sample.
- d** Puncture resistance
Between 0 and 4, based on the amount of force required to pierce the sample with a standard sized point.

x means that this performance is not tested.



BCL GLOVE LTD
 21 Parc-Industriel, Saint-Pacôme
 (Quebec) Canada G0L 3X0
 T 418 852-2098 F 418 852-3330
info@akka.ca www.akka.ca